

Beverage Stabilization

SIHA CARBOGRAN GE

1 B 5.3.4 · SH
10/2007

SIHA CARBOGRAN Ge is a specially formulated activated carbon with vegetable origin for the use in the beverage industry with mainly deodorizing properties. This highly pure carbon of vegetable origin is used to correct aroma and flavour defects in beverages.

Through a special, very gentle activation process the pore structure of the activated carbon is made specially capable of binding undesired aroma and flavour substances in beverages. Thanks to a specially developed and gentle granulation process the high adsorptive capacity of the powdered product is fully retained in the granulate.

SIHA CARBOGRAN GE can be used for mashes, musts, wines, sweet must, juices and spirits

The special advantages of SIHA CARBOGRAN GE are:

- ▶ A dust-free application because of its granulated structure.
- ▶ Adsorbs undesired aroma and flavour substances in beverages.
- ▶ Large inner surface and therefore high adsorptive capacity.
- ▶ The granulate dissolves quickly and completely in the liquid.
- ▶ Can be used directly - prior suspension not necessary.
- ▶ It builds a compact turbidity depot thanks to good sedimentation.

Application

In order to use the full adsorptive power of SIHA CARBOGRAN GE we recommend that carbon fining will be carried out in the clarified and filtered beverage to prevent displacement of the active surface through turbidities.

If used in combination with another fining agent, SIHA CARBOGRAN GE should always be added first in order not to reduce the high adsorptive capacity of the carbon.

SIHA CARBOGRAN GE can be added to the beverage without prior suspension. To ensure that the product is evenly distributed in the liquid, vigorous stirring is necessary.

Depending on the action of the agitator, the stirring time should be 10 to 20 minutes. After approx. 1 h the beverage should be thoroughly stirred once again to utilize the full adsorptive capacity of SIHA CARBOGRAN GE. As the carbon develops its adsorptive power as soon as it is added, fining takes just a few hours.

Racking by filtration should follow after two days at the latest.

Quantities required:

- ▶ To correct undesired flavours in wines due to the vintage or rot, a quantity of 30 – 50 g/hl SIHA CARBOGRAN GE is required; for best results correction should be done in the mash or in the must; a quantity of 30 – 80 g/hl can be used, depending on the strength of the foreign taste.
- ▶ To treat the desliming or separator turbidity a quantity of 80 – 100 g/hl SIHA CARBOGRAN GE is required.
- ▶ To remove rot, barrel, mould and other foreign aromas or flavours in wines and juices, 10 – 40 g/hl SIHA CARBOGRAN GE should be used.
- ▶ To treat fresh yeast sediment up to 100 g/hl SIHA-CARBOGRAN Ge is required.
- ▶ The taste of beverages can be harmonized and rounded off with just 3 – 5 g/hl SIHA CARBOGRAN GE.
- ▶ Wines with a bitter or rape taste can also be improved with 10 – 50 g/hl SIHA CARBOGRAN GE.
- ▶ To improve the flavour of spirits a quantity of at least 100 g/hl SIHA CARBOGRAN GE is required - in some cases 200 – 500 g/hl to prevent a mouldy-musty aroma or flavour.
- ▶ The activated carbon dosage for wine treatment is limited to a maximum of 100 g/hl.

Application Beer

For application in beer, pre-application tests are also recommended in order to determine the quantity required.

If the last wort is reused, color intensification and a broad, hard beer taste may be expected. This can be counteracted by adding activated carbon to the last wort with a dosage of approx. 100g/100 l.

Slight imperfections in the beer, such as yeast bitterness or a broad or slightly oxidized taste, can be corrected by using only about 5 – 10 g/100 l. (even in returned beer). However, in most cases, it is recommended to re-kräusen beer which has been treated with activated carbon (approx. 20 %) and to blend it with faultless beer depending on requirements. The carbon should be added 5 – 7 days prior to filtration, preferably by turning over the tanks. This procedure can remove even more severe imperfections, such as smoky taste or similar faults. Diacetylic taste or similar imperfections are not influenced by activated carbon.

Pre Application Test

The exact quantity of SIHA CARBOGRAN GE is best determined by performing initial tests with 100 ml of the beverage. For this, a 5 % suspension of SIHA CARBOGRAN GE is prepared. The suspension is then pipetted to 100 ml of the beverage in increasing quantities.

0,2 ml of the 5 % suspension per 100 ml beverage corresponds to a quantity of SIHA CARBOGRAN GE of 10 g/hl.

The initial tests should be carried out according to the following table:

SIHA CARBOGRAN GE suspension in 100 ml	Corresponding quantity to be added to the beverage
0.4 ml	20 g/hl
0.8 ml	40 g/hl
1.2 ml	60 g/hl
1.6 ml	80 g/hl
2.0 ml	100 g/hl

Intermediate values can be chosen accordingly.

The fining preparations should be stirred vigorously and then filtered off through a pleated filter which has been sufficiently wetted beforehand. The first 10 ml of the filtrate is discarded. The filtrate is then tasted and compared with the initial sample. The exact quantity of SIHA CARBOGRAN GE is determined by tasting the samples.

The application quantity of activated carbon for wine treatment (white wine, white wine musts) is limited by the Directive EEC n°822/87 to a maximum of 100 g/hl.

Safety

If used properly and correctly no detrimental effects of SIHA CARBOGRAN GE are known. An EU Safety Data Sheet is available on request.

Storage

SIHA CARBOGRAN GE stores well. Due to high adsorptive capacity of the carbon, it has to be stored in a dry, cool, well ventilated and odourless room. Opened packages should be sealed tight and used up quickly.

Delivery Information

SIHA CARBOGRAN GE is sold under article number 63.103 and is available in the following package sizes:

1 kg	Carton
10 x 1 kg	Carton in cardboard box
5 x 5 kg	PE-bag in cardboard box
1 x 15 kg	PE-bag

H.S. Customs Tariff. No.: 3802 10 00

Cerified Quality

SIHA CARBOGRAN GE complies with all pertinent legal requirements. It is monitored constantly during the production process to ensure consistently high quality.

These inspections cover technical function criteria as well as approval in accordance with the law governing the production and sale of foodstuffs. Strict controls are carried out immediately before and during final packing.

SIHA CARBOGRAN GE complies with the purity criteria of the International Codex for wine treatment products and with the specifications of the German Wine Code.



Reg. No. 000480 QM

All information is given to the best of our knowledge. However, the validity of the information cannot be guaranteed for every application, working practice and operating condition. Misuse of the product will result in all warranties being voided. Reproduction, even in part, is permitted only with reference to the source. Subject to change in the interest of technical progress.