

## Pure Fermentation SIHA DESTAROME™

### Aroma Yeast for Distilleries, *Saccharomyces Cerevisiae*

SIHA DESTAROME yeast is a special yeast for the fermentation of noble fruit brandy mashes and produces highly aromatic distillates. It supports the release of aroma components from the fruit during fermentation. Especially Williams pear, kirsch, plum and quince brandies gain appreciably more flavor and elegance. This also applies to noble berry varieties. It features a high temperature tolerance up to at least 59 °F (15 °C) and ferments sufficiently at lower temperatures. It ferments quite slowly but completely even with difficult mashes.

The specific advantages of SIHA DESTAROME yeast:

- Very rapid fermentation start and reliable thorough fermentation of all fruit mashes as well as excellent cold fermenting properties from approx. 50 – 59 °F (10 – 15 °C)
- Release and preservation of aroma components in the fruit
- Reliably suppresses wild yeasts and harmful bacteria
- Tolerates up to 16% alcohol by vol.
- Negligible frothing

#### Application

Basically the mashes should be treated as soon as possible. This also safeguards the alcohol yield. Longer periods of standing favor the uncontrolled reproduction of wild yeasts and unwanted bacteria. Acidification of the mash must always be done before treatment with SIHA DESTAROME yeast. Fermentation problems can be safely prevented by the dosages in the table.

These quantities are given as a guide and should be adjusted to suit the individual conditions (health of the material harvested, temperature, presence of fungicide residue, container size etc.).

The fermentation temperature range is between 50 °F and 95 °F (10 – 35 °C). The higher the alcohol content, the lower the fermentation temperature should be. The optimum fermentation temperature is 59 – 68 °F (15 – 20 °C). When using large containers, adequate cooling has to be provided.

Application	Quantity required lb/1,000 gal (g/hl) under	
	normal fermentation	difficult conditions
Drupes	0.8 – 1.7 (10 – 20)	1.7 – 3.3 (20 – 40)
Pome fruits	0.8 – 1.7 (10 – 20)	1.7 – 3.3 (20 – 40)
Berries	0.8 – 1.7 (10 – 20)	1.7 – 3.3 (20 – 40)
Topinambour	-	1.7 – 3.3 (20 – 40)
Gentian	-	1.7 – 3.3 (20 – 40)
Mashes that have stopped fermenting	-	2.5 – 5.0 (30 – 60)

SIHA DESTAROME yeast is best stirred into 10 times the amount of water mixture at 68 – 86 °F (20 – 30 °C), left for about 10 minutes, then stirred thoroughly again and added to the mash. Mixing in is unnecessary if the mash is pumped onto the yeast preparation.

The yeast can also be added directly to the mash without suspension. In this case, the period until fermentation begins is extended by only a few hours. However, to ensure reliable fermentation the yeast quantity should be increased by about 20%.

Ensure that it is distributed well.

#### Product Characteristics

Selection objectives were high fermentation activity and vitality. SIHA DESTAROME yeast exhibits a favorable course of fermentation with a high degree of final fermentation. Wild yeasts and unwanted bacteria are suppressed. Aromas contained in the fruit can be better released by the yeast.

SO<sub>2</sub> quantities up to 0.7 lb/1,000 gal (80 mg/l) are tolerated by the yeast without difficulty.

SO<sub>2</sub> contents in the mash are generally reduced during fermentation.

The yeast can produce up to 16% alcohol by volume. The practical alcohol yield is approximately 47% of the sugar content. For each lb (kg) of sugar fermented, approx. 247kJ (546 kJ)/59 kcal (130 kcal) of heat is released.



## Safety

---

No technical safety data are given for SIHA DESTAROME yeast as this product goes directly into the production of foodstuffs.

There is no danger for personnel and the environment during storage, handling and transportation.

## Storage

---

SIHA DESTAROME yeast is packed in gastight aluminum foil using inert gas. The package is vacuum-sealed and can be easily checked for intactness.

The yeast can be stored in an undamaged package at 39 – 50 °F (4 – 10 °C) for four years. It can be stored for a short time in an undamaged package at temperatures up to 68 °F (20 °C).

Opened packages should be used up immediately.

## Delivery Information

---

SIHA DESTAROME yeast is sold under article no. 93.160 and is available in the following package sizes:

1.1 lb (500 g)      aluminum sandwich foil block pack  
20 x 1.1 lb (500 g) aluminum sandwich foil block pack  
in carton

## Certified Quality

---

SIHA DESTAROME yeast is monitored regularly during the production process to ensure consistently high quality. These inspections cover technical function criteria as well as compliance with the law governing the production and sale of foodstuffs. Strict controls are also carried out immediately before and during final packing.

### North America

44 Apple Street  
Tinton Falls, NJ 07724  
Toll Free: 800 656-3344  
(North America only)  
Tel: +1 732 212-4700

### China

No. 3, Lane 280,  
Linhong Road  
Changning District, 200335  
Shanghai, P.R. China  
Tel: +86 21 5200-0099

### Europe/Africa/Middle East

Auf der Heide 2  
53947 Nettersheim, Germany  
Tel: +49 2486 809-0

Friedensstraße 41  
68804 Altludersheim, Germany  
Tel: +49 6205 2094-0

An den Nahewiesen 24  
55450 Langenlonsheim, Germany  
Tel: +49 6704 204-0

### Singapore

4 Loyang Lane #04-01/02  
Singapore 508914  
Tel: +65 6825-1668

### Brazil

Rua Clark, 2061 - Macuco  
13279-400 - Valinhos, Brazil  
Tel: +55 11 3616-8400

**For more information, please  
email us at [filtration@eaton.com](mailto:filtration@eaton.com)  
or visit [www.eaton.com/filtration](http://www.eaton.com/filtration)**

EN  
1 B 2.2.5.3  
12-2016

© 2016 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.



Powering Business Worldwide