

Pure Fermentation

uvaferm BDX

1 B 2.2.20 · ISc
09/2004

(saccharomyces cerevisiae)

uvaferm BDX is a specially selected dry active yeast, which is particularly beneficial for the fermentation of red wine must and red wine mash. The special advantages are color extraction and a balanced tannin structure. uvaferm BDX is very suitable for spicy, deep red wines (Dornfelder, Cabernet Sauvignon, Cabernet Franc, Merlot).

The specific advantages of uvaferm BDX:

- ▶ Moderate nutrient requirements
- ▶ Wide temperature range
- ▶ Increased extraction of polyphenols
- ▶ Quickly displaces wild yeasts and bacteria thanks to "killer characteristics"
- ▶ Rapid start of fermentation and main fermentation
- ▶ Low formation of undesirable fermentation by-products

Application

As a basic rule, musts should be inoculated with uvaferm BDX as early as possible. Longer maceration time favour uncontrolled multiplication of wild yeasts and undesirable bacteria. Fermentation problems are reliably prevented with the following dosage:

Application	Quantity (g/hl)	
	normal	difficult fermentation conditions
Red wine mash	15 – 25	30 – 40
Red wine must	15 – 20	30 – 35

The quantities stated are guide values. They should be adapted to the individual requirements depending on the health of the grapes, the temperature, and the batch size etc. For large batches, adequate cooling must be ensured.

uvaferm BDX is best stirred into a 10:1 must/water mixture at 35 – 40 °C, stirred again after approximately 15 minutes and added to the must.

The optimum fermentation temperature is between 24 – 28 °C, the minimum starting temperature is 18 °C. uvaferm BDX should only be added to heated must or mash after recooling or rather cooling to 20 °C.

Addition of 600 mg SIHA Vitamin B1 (2 tablets) to 1000 l of wine creates even better multiplication, fermentation and metabolism conditions. For final fermentation of stucked wines, we recommend adding an additional dose of 10 g/hl of SIHA PROFERM® Plus.

Under these conditions it is beneficial to accustom the yeast to the fermentation conditions. This is best achieved by adding the quantity of yeast required for the total quantity of wine to approximately 10 % of the total product to be fermented and fermenting until approximately half the sugar present is used up. This mixture is then added to the remaining 90 % of the wine for final fermentation. Yeasts adapted in this way usually start fermenting more quickly and have a lower tendency to die off than if they are added directly to the total quantity.

Product Characteristics

Wines fermented with uvaferm BDX have a distinct bouquet that is typical for their variety and a balanced tannin structure. Selection over several years enabled us to increase the extraction of polyphenols and therefore the color yield. Increased glycerin formation increases the "mouthfeel" and gives the wine volume.

uvaferm BDX shows an advantageous fermentation curve with high final degree of fermentation. Wild yeasts and undesirable bacteria are suppressed. uvaferm BDX generates no undesirable fermentation by-products such as SO₂, H₂S, acetaldehyde, pyruvate, α-ketoglutaric acid, volatile acid or ester.

uvaferm BDX can produce up to 16 percent alcohol by volume. The practical alcohol yield is approximately 47 % of the sugar to be fermented. For each kg of sugar fermented, approx. 546 kJ (130 kcal) of heat is released.

Safety

No safety information has to be provided for uvaferm BDX, since the product is used directly for food production. There are no known risks to humans or the environment during storage, handling and transport of the product.

Additional Notes: generally not harmful to water according to the German VwVwS regulations of 1999 (Administrative Regulation on the Classification of Substances Hazardous to Waters into Water Hazard Classes).

Storage

uvaferm BDX is packed in air-tight multi-layer aluminum film in an inert gas atmosphere. The integrity of the vacuum pack is easy to monitor.

In undamaged packaging, uvaferm BDX can be stored for three years at 4 – 10 °C. Short-term storage at 20 °C is acceptable. Once a package has been opened, it should be used up as soon as possible.

Delivery Information

uvaferm BDX has the article number 93.211 and is supplied in the following packaging units:

500 g block pack with laminated aluminum film
20 x 500 g block pack with laminated aluminum film
 (carton)

HS customs tariff: 2102 10 90

Cerified Quality

During the production process, uvaferm BDX is continuously monitored to ensure consistently high quality.

These inspections cover technical function criteria as well as conformance with the relevant laws governing the production and sale of foodstuffs. Strict controls are carried out immediately before as well as during final packaging.

uvaferm BDX conforms to the purity regulations of the International OIV Code for wine treatment products and to the regulations of the German Wine Ordinance. Please pay attention to the national laws.



Reg. No. 000480 QM

All information is given to the best of our knowledge. However, the validity of the information cannot be guaranteed for every application, working practice and operating condition. Misuse of the product will result in all warranties being voided. Reproduction, even in part, is permitted only with reference to the source. Subject to change in the interest of technical progress.